

CANTICO

model CX8



CANTICO
model CX8

CANTICO

model CX8

Specifications:

Sensitivity: 94 db/1W/1m - 8 Ohm

Power Rating: 400W Continuous Program Power

Frequency Response: 40 Hz - 20 KHz

Configuration: Two ways Coaxial with one energy filler for the low end
in a proprietary dual transmission line configuration

Drivers: One Coaxial Unit (8" Woofer + 1.4" Compression Driver)
one 8" rear firing woofer

Cabinet: 30mm MDF internally braced, 15 mm Real wood + 20mm
MDF composite side walls

Cabling: Cardas Copper Litz, Oversized Binding Posts

Crossover: Two ways, single wiring with supertweeter output

Dimensions (cm) : 32 W x 38 D x 120 H. Weight 62 Kg each

Entirely hand built in Italy

New 2012 version with:

- 10 mm steel base
- 10 mm machined aluminium top
- custom 3 metal (brass/aluminium alloy/hardened steel) adjustable
cone spikes with aluminium bases
- Cardas copper Litz cabling

NEO version available featuring:

- Neodymium magnet hand matched drivers
- Mundorf Supreme crossover components
- Stainless steel mounting hardware
- Copper Cardas binding posts
- Creaktiv Systems electro-smog reduction system built in

